



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-26.5GHz
Dielectric Withstanding Voltage	≥1000V
VSWR	≤1.15
Insertion Loss	0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium bronze gildibng
Dielectric	PEI
Body/Nut	Stainless steel SUS303,passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc					
		CHK						
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model NMD3.5M2.4F NMD3.5Male 2.4 Female Connector					
		PRODUCT SPEC						
		APPLICATION SPEC						
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO			
			CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1	SHEET 1 OF 1	RVE 1